

## **SPS150 P540 N2 EP D12 R (for PP Geo or Carpet)**

**The following specifications and pictures are only examples. The actual specifications have to be negotiated.**

- 2 colours
- 6 harness drives
- excentric device EP 10 with 6 cams
- shed formation EP
- 2 machines with whip roller / deflecting roller
- 1 machine with warp tensioner device
- let off device electric
- take up drive mechanic
- 3 contact bars
- 4 harness frames
- guide teeth block or single on customer's demand
- 2 accumulators
- 1 spool truck
- automatic pick finding device
- automatic shed formation device
- projectile brake
- lubrication GS compact
- weft brake electronic, type on customer's demand
- take-up roller mechanic
- take-up roller D=160 mm
- pressure roller D=133 mm
- prepared for half warp beam with differential
- prepared for warp beam D=150/1016 mm
- 2 warp beam gear wheels
- 2 bearing rings
- 2 clamping flanges
- 1 intermediate warp beam bearing
- 26 projectiles, type on customer's demand
- no cloth roller
- optional: batch winder
- SU/FA side tucking unit
- speed: 265 rpm max; 240 rpm on full size
- weft insertion 1300 m/min
- CE certification complying with the latest standards

Price: on request and depending on customers' specification.  
EXW Wettringen, Germany

